



CÔNG TY TNHH TM-SX-DV ĐÔNG HẢI

544/23 Lý Thường Kiệt, P7, Q.TB
Tel: 9713956 – 9008843 Fax: 9712069

www.dohaco.com



No.

JF-500

Name

JF-500 Stainless Steel Flexible Joint

The newly developed product, JF-500 VERSA JOINT, can substitute the rubber vibration. In piping system, when consider the quality, character and economy of product. It can get best effect to absorb the vibration and thermal expansion.

Script

1. Absorbing in vibration and noise which making by pump and air compressor.
2. Connecting pipe line of ship engines' cooling system.
3. Air-Conditioning, Fire-Protection and steam system of piping.
4. General piping system.

JF-500 Specification

Nominal Bore		Total Length	Bellows			Axial Movement		Working Pressure
			O.D.	Corr. No.	Ply			
Ins	mm	mm	mm			mm	mm	kg/cm ²
1-1/2	40	150	56.0	22	1	+10	-10	10
2	50	150	70.0	20	1	+10	-10	10
2-1/2	65	150	86.5	19	1	+10	-10	10
3	80	150	101.5	18	1	+10	-10	10
4	100	150	128.0	14	1	+10	-10	10
5	125	150	156.5	12	1	+10	-10	10
6	150	150	183.5	11	1	+10	-10	10
8	200	200	234.0	15	1	+10	-10	10
10	250	200	289.0	13	1	+10	-10	10
12	300	200	341.0	12	1	+10	-10	10

JF-500H Specification

Nominal Bore		Total Length	Bellows			Axial Movement		Working Pressure
			O.D.	Corr. No.	Ply			
Ins	mm	mm	mm			mm	mm	kg/cm ²
1-1/2	40	150	56.0	22	1	+10	-10	20
2	50	150	70.0	20	1	+10	-10	20

2-1/2	65	150	86.5	17	2	+10	-10	20
3	80	150	101.5	16	2	+10	-10	20
4	100	150	128.0	14	2	+10	-10	20
5	125	150	156.5	12	2	+10	-10	20
6	150	150	183.5	11	2	+10	-10	20
8	200	200	234.0	15	2	+10	-10	20
10	250	200	289.0	13	2	+10	-10	20
12	300	200	341.0	12	2	+10	-10	20

